Maximum suggested horsepower 70 HP - 51 KW												
	Total width	Y70	<b>←</b>				<b>6</b> -29	4-4		<u> </u>		I
	Working width		IN	СМ	IN	СМ	HP/KW	L₿S	KG	IN	СМ	Nr.
<b>6∵3</b>	Min. suggested horsepower	100	41	103	39	100	30/22	1014	460	12	30	4
		115	46	118	45	115	30/22	1058	480	12	30	4
Δ <u>-</u> Δ	Weight	130	55	140	54	137	35/26	1235	560	12	30	6
	Maximum working depth	145	60	152	59	149	35/26	1301	590	12	30	6
ļ.		160	66	167	65	164	40/29	1356	615	12	30	6
<b>+</b>	Number of spades	175	72	183	71	180	50/37	1587	720	12	30	8
		190	79	201	78	198	55/40	1653	750	12	30	8
		205	81	207	80	204	60/44	1720	780	12	30	8



www.celli-usa.com Toll Free: 1-877-591-4790

**Y70** 

## **SPADING MACHIN9**



## THE CONCEPT

Spading machines are tillage equipment largely appreciated in several working conditions and applications, such as:

- WR ZRUN ZLWKRXW LQ H[WUHPHO\ ZHW
- WR UHPRYH Wsko*i*H hardpan, that is the layer of compacted soil in depth

- . \$OVR LW UHTXLUH ORTZCHNICAL traction SRZHU WKXV LW SPECIFICATIONS HIILFLHQWO\ ab-VRUEV WKH
- 'R QRW FRPSDFW WKH \R(50 KW)

WUDFWRU SRZHU

WR SDLOWDLDOO\ underground FURS

DAVEROPHENA VIthrank-WERXW WR4HOFOROGAN/pleEteDNFN

WR ZRUN XnaximMirk D WR OLPLW VRLO HURV Light tailing ZRUNLQJ GHSWK RI also FVPKH ZDVK DZD\ RI

E & W JVKRVP and steeply sloping soil, because the tilled soil is composed of medium size clods.

- maximum horse power: 70
  - 4 speed gearbox for 540 rpm PTO
  - · grease lubrication
  - · 3 point hitch cat.2
  - flap
  - · working depth adjustment by skids
  - · drive shaft with clutch
- spades: 210x162 mm (models 100-130-145-175-190); 210x192 mm (models 115-160-205)
- · safety protections