

Maximum suggested horsepower ► **70 HP**

	Total width
	Working width
	Side-shift
	Min. suggested horsepower
	Weight
	Number of blades

B									
	IN	CM	IN	CM	IN-IN CM-CM	HP	LBS	KG	Nr.
<b>105</b>	49	124	43	109	22 - 28 56 - 71	35	717	325	24
<b>130</b>	59	150	53	135	26 - 26 66 - 66	40	805	365	30
<b>155</b>	69	175	63	160	31 - 31 79 - 79	45	893	405	36
<b>180</b>	79	201	73	185	36 - 36 91 - 91	55	981	445	42
<b>205</b>	89	226	83	211	41 - 41 104 - 104	60	1080	490	48



www.celli-usa.com  
Toll Free: 1-877-591-4790

**B**

The rotary tiller model **B** is one of the most tested and reliable among the Celli machines. At least 15,000 units have been sold all over the world to be used in a variety of working situations and in very different soil conditions.

High quality technical solutions have been adopted: box section frame, special sealing system to protect the rotorshaft bearings, sturdy gearbox designed and built by Celli, thick rear cover well shaped to get an ideal finishing and levelling of the soil.



## FIXED ROTARY TILLER

### TECHNICAL SPECIFICATIONS

- Maximum horsepower 70 HP
- 4 speed gearbox for 540 rpm PTO
- Gear side drive
- 3 point hitch cat. 3
- L-shaped blades: 80x7 mm (6 blades each flange, side blades leaning inwards)
- Working depth about 8.6"
- Rear tailgate adjustment by chain
- Food stand
- Drive shaft with clutch
- Removable safety protections

### OPTIONAL ACCESSORIES

- 1 speed gearbox (184 rpm) for 540 rpm PTO
- C-shaped blades
- Side blades leaning outwards
- Off-set version Bolted double flanges
- Rear rollers at origin
- Higher gearbox support