













Maximum recommended horsepower

170 HP









	Total width
	Working width
	Side shift
	Min. recommended horsepower
	Machine weight
	Number of blades







D%70									
	IN	CM	IN	CM					in-in cm-cm
205	91	231	83	211	41 - 41 104 - 104	100	1874	850	48
& \$	101	256	93	236	46 - 46 117 - 117	110	1984	900	54
255	111	282	102	259	51 - 51 129 - 129	120	2044	927	60
280	121	307	112	284	56 - 56 142 - 142	130	2205	1000	66
305	131	333	122	310	61 - 61 155 - 155	140	2315	1050	72



www.celli-usa.com
Toll Free: 1-877-591-4790

PIONEER 170

P170F															
	IN	CM	IN	CM		HP	LBS	KG	LBS	KG	LBS	KG			Nr.
230	101	256	93	236	110	2469	1120	2469	1120	2734	1240	2579	1170	45	72
255	111	282	102	259	120	2635	1195	2635	1195	2910	1320	2734	1240	50	80
280	121	307	112	284	130	2800	1270	2800	1270	3064	1390	2910	1320	55	88
305	131	333	122	310	140	2954	1340	2954	1340	3241	1470	1086	493	60	96

	Machine weight with cage roller
	Machine weight with spikes roller
	Machine weight with packer roller
	Machine weight with spiral roller
	Number of spikes for frangor models
	Number of tines for frangor models

PIONEER 170

FRESA (P170)

Rotary tillers with "C" or "L" type blade rotor and side skids

FRANGOR (P170F)

With rear roller and spike or straight tine rotor

ROTARY TILLERS and FRANGOR

**ALSO AVAILABLE IN
REVERSIBLE ROTARY
TILLER VERSION**



P170F



www.celli-usa.com
Toll Free: 1-877-591-4790

PIONEER 170

FRANGOR

The Frangor version is recommended for seedbed preparation when thorough soil refinement is required. It is different from the rotator tiller version due to the following modifications:

- rotor shaft fitter with either spikes or straight tines for accurate soil finishing. The rotor shaft rotates faster than the rotary tiller
- rear swinging articulated tailgate that offers a wide range of adjustment positions
- rear levelling roller (available in cage, spikes and packer models)

STRONG POINTS

1. **Main Frame:** box section frame, unbendable.
2. **Gearboxes:** designed, manufactured and guaranteed by Celli.
3. **Sealing system:** steel seals to protect the rotor shaft bearings.
4. **Wear resistance:** special materials are used in critical points for wear.




Spikes Roller



Spiral Roller



Cage Roller



Packer Roller

ACCESSORIES

- 2-speed gearbox for 1000 rpm with rear PTO
- 4-speed gearbox for 540 rpm PTO
- 4-speed gearbox for 540 rpm PTO (P170)
- 2-speed gearbox for 540 rpm PTO (P170F)
- 2-speed gearbox for 1000 rpm with rear PTO (P170F)
- Oil cooling kit with radiator
- C-shaped blades (P170)
- Straight tines rotor (P170F)
- Side blades leaning outwards (P170)
- 10 mm C-shaped blades or L-shaped blades (P170)
- Rotor with double welded flange and 10 mm blades (P170)
- Rotor with quick blade release system, blades 10 mm thick (P170)
- Set of 2 front wheels
- Rear rubber/steel wheels fitted with arms and reinforcement cross bar
- Side skids (P170F)
- Counterplates (P170)
- Front track eraser
- Front sod breaking discs
- Hydraulic kit for roller adjustment
- Hydraulic kit for tailgate adjustment
- Rear hydraulic hitches for seeder



TECHNICAL SPECIFICATIONS

- Maximum horsepower 170 HP
- PTO 2-speed gearbox for 1000 rpm
- Side drive: gears
- 3 point hitch cat. 2 and cat. 3
- Swinging front linkages
- Rear tailgate, adjustable with threaded bar
- Cage roller, \varnothing 440 mm adjustable with threaded bar (P170F)
- L-shaped blades: 80x8 mm (6 blades each flange, side blades leaning inwards) (P170)
- Spikes: 30x30 mm L= 170 mm (P170F)
- Working depth: 10" (P170F): 8" (P170)
- Side skids
- Front stand
- Drive shaft with clutch
- Removable safety devices